

Specification Sheet

Part Number: FPU25BU-25M

Highly durable spiral metallic conduit provides extra flexibility and delivers a high degree of compression strength and impact resistance. Polyurethane cover provides high abrasion resistance and performance in low temperature applications.

Provides ingress protection performance to IP65 when used with FSU-styled fittings.

Low fire hazard cover rated UL94 V0.

Halogen Free.



Met Conduit, Extra Flex, 0.75" (25mm) Dia, Galvanized Steel w/Halogen Free Polyurethane Cover, Blue, 82ft/Reel

Article Number 166-90679

Type FPU25BU-25M

Color Blue (BU)

Quantity Per reel

Product Description An extra flexible, galvanized steel conduit with a smooth, oil-resistant and halogen free polyether + polyurethane coating. FPU series is a spiral constructed, non-UL rated metallic conduit used in applications that demand higher levels of bending and impact protection. Designed for low temperature applications where mechanical strength and halogen free materials are required. Use with HelaGuard FSU Metallic Fittings for IP65 performance.

Short Description	Met Conduit, Extra Flex, 0.75" (25mm) Dia, Galvanized Steel w/Halogen Free Polyurethane Cover, Blue, 82ft/Reel
Global Part Name	FPU25BU-25M-GS/PUR-BU
Diameter D (Imperial)	0.83
Diameter D (Metric)	21.1
Outside Diameter OD (Imperial)	1.02
Outside Diameter OD (Metric)	26.0
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	25.0
Material	Galvanised Steel (GS) Polyurethane resin (PUR)
Material Shortcut	GS PUR
Flammability	UL 94 V-0
Halogen Free	Yes
Operating Temperature	-40°F to +212°F (-40°C to +100°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant Yes

Package Quantity (Imperial) 82

Package Quantity (Metric) 25.0

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)