

Specification Sheet

Part Number: LTPPU20B-25M

Flexible metallic conduit provides liquid-tight performance to IP66 + IP67 + IP68 + IP69 when used with LTP or LTPUL fittings.

Helically wound (spiral) galvanized steel core with an interlocking design delivers high degree of compression strength and impact resistance.

Polyurethane cover resists oil and will not crack or breakdown in low temperature applications.

Low fire hazard cover rated UL94 V0.

Manufactured to UL360 size requirements.

Halogen Free.



Liquid-Tight Met Conduit, Flex, 0.50" (20mm) Dia, Galvanized Steel w/Halogen Free Polyurethane Cover, Black, 82ft/Reel

Article Number	166-90716
Type	LTPPU20B-25M
Color	Black (BK)
Quantity Per	reel

Product Description	A flexible, liquid tight galvanized steel conduit with a smooth oil resistant polyurethane coating. LTPPU series is a halogen free conduit designed for low temperature performance, and has excellent flame retardation, limited smoke and low toxicity properties. Use with LTP or LTPUL series metallic fittings for IP66 + IP67 + IP68 + IP69 ratings. May be used in hazardous locations when accompanied with LTPUL or EXD metallic fittings.
Short Description	Liquid-Tight Met Conduit, Flex, 0.50" (20mm) Dia, Galvanized Steel w/Halogen Free Polyurethane Cover, Black, 82ft/Reel
Global Part Name	LTPPU20B-25M-GS/PUR-BK
Length L (Imperial)	82.0
Length L (Metric)	25.0
Diameter D (Imperial)	0.63
Diameter D (Metric)	16.0
Outside Diameter OD (Imperial)	0.83
Outside Diameter OD (Metric)	21.1
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	20.0
Material	Polyurethane resin (PUR) Galvanised Steel (GS)

Material Shortcut	PUR GS
Flammability	UL 94 V-0
Halogen Free	Yes
Operating Temperature	-40°F to +212°F (-40°C to +100°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	82
Package Quantity (Metric)	25.0