

Specification Sheet

Part Number: LTPPU25BU-25M



Liquid-Tight Metallic Conduit, Flexible, 0.75" (25mm) Dia, Galvanized Steel w/Halogen Free Polyurethane Cover, Blue, 82ft/Reel

Article Number 166-90725

Type LTPPU25BU-25M

Color Blue (BU)

Features & Benefits

- Flexible metallic conduit provides liquid-tight performance to IP66 + IP67 + IP68 + IP69 when used with LTP or LTPUL fittings.
- Helically wound (spiral) galvanized steel core with an interlocking design delivers high degree of compression strength and impact resistance.
- Polyurethane cover resists oil and will not crack or breakdown in low temperature applications.
- Low fire hazard cover rated UL94 V0.
- Manufactured to UL360 size requirements.
- Halogen Free.

Quantity Per reel

Product Description	A flexible, liquid tight galvanized steel conduit with a smooth oil resistant polyurethane coating. LTPPU series is a halogen free conduit designed for low temperature performance, and has excellent flame retardation, limited smoke and low toxicity properties. Use with LTP or LTPUL series metallic fittings for IP66 + IP67 + IP68 + IP69 ratings. May be used in hazardous locations when accompanied with LTPUL or EXD metallic fittings.
Short Description	Liquid-Tight Metallic Conduit, Flexible, 0.75" (25mm) Dia, Galvanized Steel w/Halogen Free Polyurethane Cover, Blue, 82ft/Reel
Global Part Name	LTPPU25BU-25M-GS/PUR-BU
Technical Description	Manufacturer Reference Number: LTPPU25BU-25M
Length L (Imperial)	82.0
Length L (Metric)	25.0
Diameter D (imperial)	0.83
Diameter D (metric)	21.0
Outside Diameter OD(Imperial)	1.04
Outside Diameter OD(metric)	26.4
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	25.0

Material	Polyurethane resin (PUR) Galvanised Steel (GS)
Material Shortcut	GS PUR
Flammability	UL 94 V0
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +212°F (-40°C to +100°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	82
Package Quantity (Metric)	25.0
Weight (Metric)	12.58
Weight (Imperial)	27.7