

Specification Sheet

Part Number: LTBRDP50B-10M


Flexible metallic conduit provides liquid-tight performance to IP66 + IP67 + IP68 + IP69 when used with LTP or LTPUL fittings.

Helically wound (spiral) galvanized steel core with an interlocking design delivers high degree of compression strength and impact resistance.

Smooth PVC cover resists oil and grease and will not wrinkle or crack when conduit is bent; also provides corrosion resistance.

Center layer of galvanized steel overbraid provides EMC screening 60dB @ 1MHz.

Manufactured to UL360 requirements.



Liquid-Tight Met Conduit, Flex, 1.5" (50mm) Dia, Galv Steel core w/Galv Inner Braid and PVC Cover, Black, 32.8 ft/Reel

Article Number	166-90734
Type	LTBRDP50B-10M
Color	Black (BK)
Quantity Per	reel

Product Description	A flexible, liquid-tight galvanized steel conduit with a smooth, oil-resistant PVC coating and galvanized steel middle braid. LTBRDP series conduit is designed for liquid-tight applications where a high degree of corrosion resistance is required along with EMC screening. Use with HelaGuard LTP or LTPUL series metallic fittings for IP66 + IP67 + IP68 + IP69 ratings.
Short Description	Liquid-Tight Met Conduit, Flex, 1.5" (50mm) Dia, Galv Steel core w/Galv Inner Braid and PVC Cover, Black, 32.8 ft/Reel
Global Part Name	LTBRDP50B-10M-GS/PVC-BK
Length L (Imperial)	32.8
Length L (Metric)	10.0
Diameter D (Imperial)	1.59
Diameter D (Metric)	40.4
Outside Diameter OD (Imperial)	1.89
Outside Diameter OD (Metric)	47.9
Nominal Diameter (Imperial)	1.5
Nominal Diameter (Metric)	50.0
Material	Galvanised Steel (GS) Polyvinylchloride (PVC)

Material Shortcut	PVC GS
Flammability	Self-extinguishing according to EN IEC 61386-1
Halogen Free	No
Operating Temperature	-4°F to +221°F (-20°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	82
Package Quantity (Metric)	10.0

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)