


## Specification Sheet

Part Number: LTBRDP50B-10M



Liquid-Tight Metallic Conduit, Flexible, 1.5" (50mm) Dia, Galvanized Steel core w/Galvanized Inner Braid and PVC Cover, Black, 32.8 ft/Reel

<b>Article Number</b>	166-90734
<b>Type</b>	LTBRDP50B-10M
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Flexible metallic conduit provides liquid-tight performance to IP66 + IP67 + IP68 + IP69 when used with LTP or LTPUL fittings.</li><li>• Helically wound (spiral) galvanized steel core with an interlocking design delivers high degree of compression strength and impact resistance.</li><li>• Smooth PVC cover resists oil and grease and will not wrinkle or crack when conduit is bent; also provides corrosion resistance.</li><li>• Center layer of galvanized steel overbraid provides EMC screening 60dB @ 1MHz.</li><li>• Manufactured to UL360 requirements.</li></ul>
<b>Quantity Per</b>	reel

**Product Description**

A flexible, liquid-tight galvanized steel conduit with a smooth, oil-resistant PVC coating and galvanized steel middle braid. LTBRDP series conduit is designed for liquid-tight applications where a high degree of corrosion resistance is required along with EMC screening. Use with HelaGuard LTP or LTPUL series metallic fittings for IP66 + IP67 + IP68 + IP69 ratings.

**Short Description**

Liquid-Tight Metallic Conduit, Flexible, 1.5" (50mm) Dia, Galvanized Steel core w/Galvanized Inner Braid and PVC Cover, Black, 32.8 ft/Reel

**Global Part Name**

LTBRDP50B-10M-GS/PVC-BK

**Technical Description**

Manufacturer Reference Number: LTBRDP50B-10M

**Length L (Imperial)**

32.8

**Length L (Metric)**

10.0

**Diameter D (imperial)**

1.59

**Diameter D (metric)**

40.4

**Outside Diameter OD(Imperial)**

1.89

**Outside Diameter OD(metric)**

47.9

**Nominal Diameter (Imperial)**

1-1/2

**Nominal Diameter (Metric)**

50.0

**Material**

Galvanised Steel (GS) Polyvinylchloride (PVC)

**Material Shortcut**

PVC GS

**Flammability**

Self-Extinguishing according to EN IEC 61386-1

**Halogen free**

No

**Operating Temperature (Metric)**

-4°F to +221°F (-20°C to +105°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

82

**Package Quantity (Metric)**

10.0

**Weight (Metric)**

12.4

**Weight (Imperial)**

27.3