

## Specification Sheet

Part Number: FW20



HelaGuard M20 Fiber Sealing Washer, 20mm Dia, Vulcanized Fiber, Red, 10/pkg

<b>Article Number</b>	166-90737
<b>Type</b>	FW20
<b>Color</b>	Red (RD)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Rugged, tough material (78 Shore D Hardness) for tighter seal.</li><li>• Protects against water and dust.</li><li>• For metric or NPT threads.</li><li>• Resistant to oil.</li></ul>
<b>Quantity Per</b>	pack
<b>Product Description</b>	Vulcanized Fiber Sealing Washer used with metallic threaded fittings. Suitable for Metric or NPT threaded fittings.
<b>Short Description</b>	HelaGuard M20 Fiber Sealing Washer, 20mm Dia, Vulcanized Fiber, Red, 10/pkg
<b>Global Part Name</b>	FW20-VF-RD

<b>Variant</b>	Seal Washer
<b>Outside Diameter OD(Imperial)</b>	1.02
<b>Outside Diameter OD(metric)</b>	26.0
<b>Nominal Diameter (Imperial)</b>	13/16
<b>Nominal Diameter (Metric)</b>	20
<b>Wall Thickness WT (Metric)</b>	1.6
<b>Mounting Hole Diameter D (Metric)</b>	20.0 mm
<b>Material</b>	Vulcanised Fibre (VF)
<b>Material Shortcut</b>	VF
<b>Operating Temperature (Metric)</b>	-58°F to +275°F (-50°C to +135°C)
<b>Package Quantity(Imperial)</b>	10
<b>Package Quantity (Metric)</b>	10
<b>Customs Number</b>	3926909988

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)