

Specification Sheet

Part Number: FU25-M25-M



Nickel plated brass compression fitting used with FU-x series flexible metallic conduit.

Two part fitting comprised of shell and body with external metric thread delivers IP40 ingress protection.

Suitable for knockouts and secured with a metric threaded locknut.

Metallic Compression Fitting, Fixed Straight, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Article Number 166-90765

Type FU25-M25-M

Color Metal (ML)

Quantity Per pack

Product Description Two-part nickel plated brass straight fitting with fixed external metric thread. Fitting comprised of shell and body suitable for knockout entries. For use with FU-x flexible metal conduit.

Short Description Metallic Compression Fitting, Fixed Straight, M25 Metric Thread, 3/4" (25mm) Dia, NPB Metal, 10/pkg

Global Part Name FU25-M25-M-NPB-ML

Technical Description

Manufacturer Reference Number: FU25-M25-M

Length L (Imperial)

1.16

Length L (Metric)

29.5

Variant

Straight

Height H (Imperial)

1.14

Height H (Metric)

29.0

Nominal Diameter (Imperial)

0.75

Nominal Diameter (Metric)

25.0

Material

Nickel Plated Brass (NPB)

Material Shortcut

NPB

Halogen Free

Yes

Operating Temperature

-58°F to +572°F (-50°C to +300°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	7412200000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)