

## Specification Sheet

Part Number: FU63-M63-M



Nickel plated brass compression fitting used with FU-x series flexible metallic conduit.

Two part fitting comprised of shell and body with external metric thread delivers IP40 ingress protection.

Suitable for knockouts and secured with a metric threaded locknut.

Metallic Compression Fitting, Fixed Straight, M63 Metric Thread, 2" (63mm) Dia, NPB Metal, 1/pkg

<b>Article Number</b>	166-90769
<b>Type</b>	FU63-M63-M
<b>Color</b>	Metal (ML)
<b>Quantity Per</b>	pack
<b>Product Description</b>	Two-part nickel plated brass straight fitting with fixed external metric thread. Fitting comprised of shell and body suitable for knockout entries. For use with FU-x flexible metal conduit.
<b>Short Description</b>	Metallic Compression Fitting, Fixed Straight, M63 Metric Thread, 2" (63mm) Dia, NPB Metal, 1/pkg
<b>Global Part Name</b>	FU63-M63-M-NPB-ML

**Technical Description** Manufacturer Reference Number: FU63-M63-M

**Length L (Imperial)** 1.97

**Length L (Metric)** 50.0

**Variant** Straight

**Height H (Imperial)** 2.76

**Height H (Metric)** 70.0

**Nominal Diameter (Imperial)** 2.5

**Nominal Diameter (Metric)** 63

**Material** Nickel Plated Brass (NPB)

**Material Shortcut** NPB

**Halogen Free** Yes

**Operating Temperature** -58°F to +572°F (-50°C to +300°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 1

**Package Quantity (Metric)** 1

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)