

## Specification Sheet

Part Number: 166-90783



HelaGuard Non-Metallic Ultra IP68 Fitting, Straight, .50" NPT Thread, .50" Dia., PA66, Black, 1/pkg

**Article Number** 166-90783

**Type** HGU050-S-0500

**Color** Black (BK)

### Features & Benefits

- Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability.
- True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits.
- All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.
- PA66 nylon material has high resistance to salts, oils, weak acids, and solvents.
- Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.

**Quantity Per** pack

<b>Product Description</b>	Straight Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection.
<b>Short Description</b>	HelaGuard Non-Metallic Ultra IP68 Fitting, Straight, .50" NPT Thread, .50" Dia., PA66, Black, 1/pkg
<b>Global Part Name</b>	HGU050-S-0500-PA66-BK
<b>Length L (Imperial)</b>	1.73
<b>Length L (Metric)</b>	44
<b>Variant</b>	Straight
<b>Outside Diameter OD(Imperial)</b>	1.26
<b>Outside Diameter OD(metric)</b>	32.0
<b>Nominal Diameter (Imperial)</b>	0.5
<b>Nominal Diameter (Metric)</b>	21
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66

<b>Flammability</b>	Self-Extinguishing
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-58°F to +275°F (-50°C to +135°C)
<b>ROHS Complaint</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Listed (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	1
<b>Package Quantity (Metric)</b>	1
<b>Customs Number</b>	3926909988