HellermannTyton

Specification Sheet

Part Number: 166-90796



HelaGuard Non-Metallic Ultra Fitting, Straight, IP68, M20 Thread, 21mm Dia, PA66, Black, 200/pkg

Article Number 166-90796

Type HGU21-S-M20B

Color Black (BK)

Features & Benefits

- Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability.
- True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits. All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force. PA66 nylon material has high resistance to salts, oils, weak acids, and solvents. External nickel-plated brass metric threads provide a extra-secure connection. Swivel feature minimizes cable twisting and provides strain relief. Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.

Quantity Per

pack

Product Description	Straight Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection.
Short Description	HelaGuard Non-Metallic Ultra Fitting, Straight, IP68, M20 Thread, 21mm Dia, PA66, Black, 200/pkg
Global Part Name	HGU21-S-M20B-PA66-BK
Length L (Imperial)	1.73
Length L (Metric)	44
Variant	Straight
Outside Diameter OD(Imperial)	1.18
Outside Diameter OD(metric)	30.0

Nominal Diameter (Imperial)

Nominal Diameter (Metric) 21

Material Polyamide 6.6 (PA66)

0.5

PA66 **Material Shortcut**

Flammability Self-Extinguishing

Halogen free Yes

Operating Temperature (Metric) -58°F to +275°F (-50°C to +135°C)

ROHS Complaint Yes

UL Listed (US and Canada) Yes

UL Listed (US Yes

Package Quantity(Imperial) 10

Package Quantity (Metric) 10

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions