

Specification Sheet

Part Number: 166-90811



HelaGuard Non-Metallic Ultra Fitting, 90-Deg Elbow, IP68, M50 Thread, 42mm Dia, PA66, Black, 2/pkg

Article Number 166-90811

Type HGU42-90-M50B

Color Black (BK)

Features & Benefits

- Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability.
- True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits.
- All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.
- Elbow features a smooth bore to ease cable installation.
- PA66 nylon material has high resistance to salts, oils, weak acids, and solvents.
- Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.

Quantity Per pack

Product Description	Elbow Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection.
Short Description	HelaGuard Non-Metallic Ultra Fitting, 90-Deg Elbow, IP68, M50 Thread, 42mm Dia, PA66, Black, 2/pkg
Global Part Name	HGU42-90-M50B-PA66-BK
Length L (Imperial)	3.86
Length L (Metric)	98.0
Variant	90° Elbow
Outside Diameter OD(Imperial)	3.27
Outside Diameter OD(metric)	83.0
Nominal Diameter (Imperial)	1-1/2
Nominal Diameter (Metric)	42
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66

Flammability	Self-Extinguishing
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
ROHS Complaint	Yes
UL Listed (US and Canada)	Yes
UL Listed (US	Yes
Package Quantity(Imperial)	2
Package Quantity (Metric)	2