

Specification Sheet

Part Number: 166-90824

Product Image

HelaGuard NM 16mm IP68 Ultra Fitting, 90-Elbow Brass Swivel, Ext M16 Thread, NPB, PA66, Black, 10/pkg

Article Number 166-90824

Type HGU16-90M-M16B

Color Black (BK)

Features & Benefits

- Integrated Sealing Technology creates a true, one-piece component that reduces installation time and provides error free installation.
- Nickel plated brass metric thread provides a secure connection even under dynamic conditions.
- Swivel thread feature minimizes cable twisting and provides strain relief.
- All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.
- Fittings deliver IP68 ingress protection against moisture and dirt.

Quantity Per pack

Product Description

Straight snap-on style fittings with nickel plated brass metric threaded fitting provides a true, one-piece component solution; seals are integrated into the fitting body. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids and solvents. Designed for fast assembly and easy removal using a small screwdriver.

Short Description HelaGuard NM 16mm IP68 Ultra Fitting, 90-Elbow Brass Swivel, Ext M16 Thread, NPB, PA66, Black, 10/pkg

Global Part Name HGU16-90M-M16B-NPB/PA66-BK

| | |
|---------------------------------------|--|
| Length L (Imperial) | 2.44 |
| Length L (Metric) | 62 |
| Variant | 90° Elbow |
| Nominal Diameter (Imperial) | 0.38 |
| Nominal Diameter (Metric) | 16 |
| Material | Polyamide 6.6 (PA66) Nickel Plated Brass (NPB) |
| Material Shortcut | PA66 NPB |
| Flammability | Self-Extinguishing |
| Halogen free | Yes |
| Operating Temperature (Metric) | -58°F to +275°F (-50°C to +135°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 10 |
| Package Quantity (Metric) | 10 |

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)