

Specification Sheet

Part Number: 166-90829

Product Image

HelaGuard NM 34mm IP68 Ultra Fitting, 90-Elbow Brass Swivel, Ext M32 Thread, NPB, PA66, Black, 10/pkg

Article Number 166-90829

Type HGU42-90M-M50B

Color Black (BK)

Features & Benefits

- Integrated Sealing Technology creates a true, one-piece component that reduces installation time and provides error free installation.
- Nickel plated brass metric thread provides a secure connection even under dynamic conditions.
- Swivel thread feature minimizes cable twisting and provides strain relief.
- All-around teeth attach firmly to corrugated conduit and deliver a high extraction force.

Quantity Per pack

Product Description

Straight snap-on style fittings with nickel plated brass metric threaded fitting provides a true, one-piece component solution; seals are integrated into the fitting body. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids and solvents. Designed for fast assembly and easy removal using a small screwdriver. UL-Listed fittings deliver IP66+IP67+IP68+IP69 ingress protection.

Short Description HelaGuard NM 34mm IP68 Ultra Fitting, 90-Elbow Brass Swivel, Ext M32 Thread, NPB, PA66, Black, 10/pkg

Global Part Name HGU42-90M-M50B-NPB/PA66-BK

Length L (Imperial)	3.46
Length L (Metric)	88
Variant	90° Elbow
Nominal Diameter (Imperial)	1-1/4
Nominal Diameter (Metric)	42
Material	Nickel Plated Brass (NPB) Polyamide 6.6 (PA66)
Material Shortcut	NPB PA66
Flammability	Self-Extinguishing
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)