

Specification Sheet

Part Number: 166-90988



Overlapping conduit design increases mechanical protection and eliminates unintentional exposure of wires caused by motion, vibration or when routed around corners.

Material is easy to use and cut - reduces installation time and labor costs.

Good impact strength; recovers quickly if crushed.

HelaGuard Non-Metallic Conduit, Double Slit, 1.50" Dia, PP, Black, 82 ft/Std. Reel

Article Number 166-90988

Type HG-DC1500

Color Black (BK)

Quantity Per roll

Product Description A standard-weight, polypropylene, corrugated two-piece conduit, each of which is slit open to ease installation and maintenance of wire and cable bundles. The interlocking construction is excellent for retrofitting projects. Polypropylene material is typically used in building construction, particularly where buried in concrete or plaster. Flexible, abrasion resistant and durable for a variety of applications.

Short Description HelaGuard Non-Metallic Conduit, Double Slit, 1.50" Dia, PP, Black, 82 ft/Std. Reel

Global Part Name	HG-DC1500-PP-BK
Length L (Imperial)	82.0
Length L (Metric)	25
Inner Diameter D (Imperial)	1.70
Inner Diameter D (Metric)	43
Outside Diameter OD (Imperial)	2.15
Outside Diameter OD (Metric)	54.5
Nominal Diameter (Imperial)	2.13
Nominal Diameter (Metric)	54
Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	Self-extinguishing according to EN IEC 61386
Halogen Free	No
Operating Temperature	-4°F to +194°F (-20°C to +90°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 82

Package Quantity (Metric) 25