

Specification Sheet

Part Number: CTN380STD



Convoluted Tubing, Slit, .38" Dia, PA6, Black with Gray Stripe, 1900ft/carton

Article Number	169-60015
Type	CTN380
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	<ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture• Tubing protects cables and wires against automotive fluids, vibration wear• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Quantity Per	carton

Product Description

HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description

Convoluted Tubing, Slit, .38" Dia, PA6, Black with Gray Stripe, 1900ft/carton

Global Part Name

CTN380-PA6-BK

Technical Description

Convoluted Tubing, Slit, 3/8" Dia., PA6, Black w/Gray Stripe

Length L (Imperial)

1900.0

Length L (Metric)

579.1

Variant

Slit

Inner Diameter D (Imperial)

0.380

Inner Diameter D (Metric)

9.65

Diameter D (imperial)

0.526

Diameter D (metric)

13.36

Outside Diameter OD(Imperial)

0.526

Outside Diameter OD(metric)

13.36

Nominal Diameter (Imperial)

3/8

Nominal Diameter (Metric)	9.65
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1900
Package Quantity (Metric)	579.10
Customs Number	3926909988

