
HellermannTyton

Specification Sheet

Part Number: 169-60552



Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Split side is ideal for applications where braided tubing or spiral wrap may

Convoluted Tubing, Slit, .75" Dia, PE, Orange, 550 ft/carton

Article Number 169-60552

Type CTP340

Color Orange (OG), High Voltage (HV)

Quantity Per carton

Product Description HellermannTyton's Convoluted Tubing, also known at Split Loom

Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold

and sunlight on cables and wires.

Short Description	Convoluted Tubing, Slit, .75" Dia, PE, Orange, 550 ft/carton
Global Part Name	CTP340-PE-OG
Length L (Imperial)	550.0
Length L (Metric)	167.6
Variant	Slit
Inner Diameter D (Imperial)	0.759
Inner Diameter D (Metric)	19.28
Diameter D (Imperial)	0.989
Diameter D (Metric)	25.12
Outside Diameter OD (Imperial)	0.989
Outside Diameter OD (Metric)	25.12
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	19.05
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127

Material Polyethylene (PE)

Material Shortcut PE

Flammability Not flame retardant

Halogen Free No

Operating Temperature -40°F to +185°F (-40°C to +85°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 550

Package Quantity (Metric) 167.60

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions