

## Specification Sheet

Part Number: 170-03010



Braided Sleeving, Expandable, Flame Retardant, 1.25" Dia, PET, Black, 50 ft/reel

**Article Number**

170-03010

**Type**

BSPFR1140

**Color**

Black (BK)

**Features & Benefits**

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

**Quantity Per**

reel

**Product Description**

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description**

Braided Sleeving, Expandable, Flame Retardant, 1.25" Dia, PET, Black, 50 ft/reel

**Global Part Name**

BSPFR1140-PET-BK

**Length L (Imperial)**

50.0

**Length L (Metric)**

15.2

**Bundle Diameter Min (Imperial)**

0.75

**Bundle Diameter Min (Metric)**

19.1

**Bundle Diameter Max (Imperial)**

1.75

**Bundle Diameter Max (Metric)**

44.5

**Diameter D (imperial)**

1.25

**Diameter D (metric)**

31.8

**Nominal Diameter (Imperial)**

1-1/4

**Nominal Diameter (Metric)**

31.8

**Material**

Polyester (PET)

**Material Shortcut**

PET

**Flammability**

FMVSS 302 UL VW-1 FAR 25 Mil-202

**Halogen free** Yes

**Operating Temperature (Metric)** -94°F to +257°F (-70°C to +125°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL 94 VW-1

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 50

**Package Quantity (Metric)** 15.24

**Customs Number** 3926909987

**Weight (Metric)** 0.363

**Weight (Imperial)** 0.8