

Specification Sheet

Part Number: 170-03013



Cuts with scissors without fraying ends enables field installations without need for hot knife.
Expands to 150% of easy installation and reduced assembly time requirements.
Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.

Braided Sleeving, Expandable, Fray Resistant, 0.75" Dia, PET, Black, 75 ft/reel

Article Number 170-03013

Type BSPSC340

Color Black (BK)

Quantity Per reel

Product Description A versatile and economical general purpose sleeving that resists fraying when cut with ordinary scissors. For use in automotive, industrial and computer applications where the wires, cables and hoses being covered endure frequent handling. It is suited for situations where access to a hot knife is either impractical or impossible.

Short Description Braided Sleeving, Expandable, Fray Resistant, 0.75" Dia, PET, Black, 75 ft/reel

Global Part Name BSPSC340-PET-BK

Length L (Imperial) 75.0

Length L (Metric) 22.9

Bundle Diameter Min (Imperial) 0.625

Bundle Diameter Min (Metric) 15.9

Bundle Diameter Max (Imperial) 1.0

Bundle Diameter Max (Metric) 25.4

Diameter D (Imperial) 0.75

Diameter D (Metric) 19.1

Nominal Diameter (Imperial) 0.75

Nominal Diameter (Metric) 19.1

Material Polyester (PET)

Material Shortcut PET

Flammability UL 94 V0

Halogen Free	Yes
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	75
Package Quantity (Metric)	22.86
Customs Number	5808100000