


## Specification Sheet

Part Number: 170-03028



Braided Sleeving, Expandable, .75" Dia, PA66 Monofilament, Black, 75 ft/reel

Article Number

170-03028

Type

BSPA66340

Color

Black (BK)

### Features & Benefits

- Resists fuels, salts and solvents, gasoline, and other common contaminants.
- Nylon monofilament construction weave offers a tight, 12 mil braid that provides full coverage but will not rot or retain moisture.
- Material performs well in wet applications and where abiding substrate has a smooth surface.
- Expands up to 150% of flat diameter for easy installation.

Quantity Per

reel

### Product Description

A pliable yet durable nylon sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion. Used on hoses, pipes, wiring harnesses and cables installed in cars, trucks, military vehicles, trains and industrial equipment. Protects delicate wiring in engine compartments and near exhaust systems or used to organize wires and breakouts in electrical harnesses.

<b>Short Description</b>	Braided Sleeving, Expandable, .75" Dia, PA66 Monofilament, Black, 75 ft/reel
<b>Global Part Name</b>	BSPA66340-PA66-BK
<b>Length L (Imperial)</b>	75.0
<b>Length L (Metric)</b>	22.9
<b>Bundle Diameter Min (Imperial)</b>	0.5
<b>Bundle Diameter Min (Metric)</b>	12.7
<b>Bundle Diameter Max (Imperial)</b>	1.25
<b>Bundle Diameter Max (Metric)</b>	31.8
<b>Diameter D (imperial)</b>	0.75
<b>Diameter D (metric)</b>	19.1
<b>Nominal Diameter (Imperial)</b>	3/4
<b>Nominal Diameter (Metric)</b>	19.1
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	Non-Flammable

**Halogen free** Yes

**Operating Temperature (Metric)** -49°F to +302°F (-45°C to +150°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 75

**Package Quantity (Metric)** 22.86

**Customs Number** 3926909987

**Weight (Metric)** 0.5

**Weight (Imperial)** 1.1