

Specification Sheet

Part Number: 170-03035

Cuts with scissors without fraying ends enables field installations without need for hot knife.

Expands to 150% of easy installation and reduced assembly time requirements.

Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.



Braided Sleeving, Expandable, Fray Resistant, 0.25" Dia, PET, Black, 100 ft/reel

Article Number 170-03035

Type BSPSC140

Color Black (BK)

Quantity Per reel

Product Description A versatile and economical general purpose sleeving that resists fraying when cut with ordinary scissors. For use in automotive, industrial and computer applications where the wires, cables and hoses being covered endure frequent handling. It is suited for situations where access to a hot knife is either impractical or impossible.

Short Description Braided Sleeving, Expandable, Fray Resistant, 0.25" Dia, PET, Black, 100 ft/reel

Global Part Name BSPSC140-PET-BK

Length L (Imperial) 100.0

Length L (Metric) 30.48

Bundle Diameter Min (Imperial) 0.156

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 0.437

Bundle Diameter Max (Metric) 11.1

Diameter D (Imperial) 0.25

Diameter D (Metric) 6.4

Nominal Diameter (Imperial) 0.25

Nominal Diameter (Metric) 6.4

Material Polyester (PET)

Material Shortcut PET

Flammability UL 94 V-0

Halogen Free	Yes
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	5808100000

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)