

## Specification Sheet

Part Number: 170-03048



Resists fuels, salts and solvents, gasoline, and other common contaminants. Nylon monofilament construction weave offers a tight, 12 mil braid that provides full coverage but will not rot or retain moisture. Material performs well in wet applications and where abiding substrate has a smooth surface. Expands up to 150% of flat diameter for easy installation.

Braided Sleeving, Expandable, 1" Dia, PA66 Monofilament, Black, 250 ft/bulk reel

**Article Number** 170-03048

**Type** BSPA66100B

**Color** Black (BK)

**Quantity Per** reel

**Product Description** A pliable yet durable nylon sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion. Used on hoses, pipes, wiring harnesses and cables installed in cars, trucks, military vehicles, trains and industrial equipment. Protects delicate wiring in engine compartments and near exhaust systems or used to organize wires and breakouts in electrical harnesses.

**Short Description** Braided Sleeving, Expandable, 1" Dia, PA66 Monofilament, Black, 250 ft/bulk reel

**Global Part Name** BSPA66100B-PA66-BK

**Length L (Imperial)** 250.0

**Length L (Metric)** 76.2

**Bundle Diameter Min (Imperial)** 0.625

**Bundle Diameter Min (Metric)** 15.9

**Bundle Diameter Max (Imperial)** 1.375

**Bundle Diameter Max (Metric)** 35.0

**Diameter D (Imperial)** 1.0

**Diameter D (Metric)** 25.4

**Nominal Diameter (Imperial)** 1

**Nominal Diameter (Metric)** 25.4

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** Non-Flammable

<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-49°F to +302°F (-45°C to +150°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	250
<b>Package Quantity (Metric)</b>	76.20
<b>Customs Number</b>	5808100000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)