

## Specification Sheet

Part Number: 170-03050

An exceptionally tough sleeving material which provides thermal protection up to 1,200°F.

Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.

Cuts easily with ordinary scissors for easy application.

UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.



Braided Sleeving, Resin Coated Fiberglass, 0.25" Dia, GF, Black, 200 ft/bulk reel

|                     |   |
|---------------------|---|
| Article Number      | 170-03050   |
| Type                | BSHTFG140B  |
| Color               | Black (BK)  |
| Quantity Per        | reel  |
| Product Description | An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress. Perfect for engine manifolds and exhaust systems or any application where fire and exceeding temperatures create a hazard to workforce and equipment. |
| Short Description   | Braided Sleeving, Resin Coated Fiberglass, 0.25" Dia, GF, Black, 200 ft/bulk reel   |

Global Part Name BSHTFG140B-GF-BK

Length L (Imperial) 200.0

Length L (Metric) 61.0

Bundle Diameter Min (Imperial) 0.1

Bundle Diameter Min (Metric) 2.54

Bundle Diameter Max (Imperial) 0.375

Bundle Diameter Max (Metric) 9.5

Diameter D (Imperial) 0.25

Diameter D (Metric) 6.4

Nominal Diameter (Imperial) 0.25

Nominal Diameter (Metric) 6.4

Wall Thickness WT (Imperial) 0.031

Wall Thickness WT (Metric) 0.79

Material Glass Fiber (GF)

|                              |                                    |
|------------------------------|------------------------------------|
| Material Shortcut            | GF                                 |
| Flammability                 | UL VW-1                            |
| Halogen Free                 | Yes                                |
| Operating Temperature        | -94°F to +1202°F (-70°C to +650°C) |
| Reach Compliant (Article 33) | Yes                                |
| ROHS Compliant               | Yes                                |
| UL Recognized (US)           | Yes                                |
| Package Quantity (Imperial)  | 200                                |
| Package Quantity (Metric)    | 60.96                              |
| Customs Number               | 7019905050                         |