

Specification Sheet

Part Number: 170-03050



Braided Sleeving, Resin Coated Fiberglass, .25" Dia, GF, Black, 200 ft/bulk reel

Article Number	170-03050
Type	BSHTFG140B
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•An exceptionally tough sleeving material which provides thermal protection up to 1,200°F.•Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.•Cuts easily with ordinary scissors for easy application.•UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.
Quantity Per	reel
Product Description	An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress. Perfect for engine manifolds and exhaust systems or any application where fire and exceeding temperatures create a hazard to workforce and equipment.

Short Description

Braided Sleeving, Resin Coated Fiberglass, .25" Dia, GF, Black, 200 ft/bulk reel

Global Part Name

BSHTFG140B-GF-BK

Length L (Imperial)

200.0

Length L (Metric)

61.0

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

0.375

Bundle Diameter Max (Metric)

9.5

Diameter D (imperial)

0.25

Diameter D (metric)

6.4

Nominal Diameter (Imperial)

1/4

Nominal Diameter (Metric)

6.4

Wall Thickness WT (Imperial)

0.031

Wall Thickness WT (Metric)

0.79

Material

Glass Fiber (GF)

Material Shortcut	GF
Flammability	UL VW-1
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +1202°F (-70°C to +650°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	200
Package Quantity (Metric)	60.96
Customs Number	7019901000
Weight (Metric)	1.81
Weight (Imperial)	4.0