

Specification Sheet

Part Number: 170-03052



Braided Sleeving, Resin Coated Fiberglass, .75" Dia, GF, Black, 200 ft/bulk reel

Article Number

170-03052

Type

BSHTFG340B

Color

Black (BK)

Features & Benefits

- An exceptionally tough sleeving material which provides thermal protection up to 1,200°F.
- Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
- Cuts easily with ordinary scissors for easy application.
- UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.

Product Description

An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress. Perfect for engine manifolds and exhaust systems or any application where fire and exceeding temperatures create a hazard to workforce and equipment.

Short Description

Braided Sleeving, Resin Coated Fiberglass, .75" Dia, GF, Black, 200 ft/bulk reel

Global Part Name

BSHTFG340B-GF-BK

Length L (Imperial)

200.0

Length L (Metric)

61.0

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

1.125

Bundle Diameter Max (Metric)

28.6

Diameter D (imperial)

0.75

Diameter D (metric)

19.1

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

19.1

Wall Thickness WT (Imperial)

0.046

Wall Thickness WT (Metric)

1.17

Material

Glass Fiber (GF)

Material Shortcut

GF

Flammability	UL VW-1
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +1202°F (-70°C to +650°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	200
Package Quantity (Metric)	60.96
Customs Number	7019901000
Weight (Metric)	5.81
Weight (Imperial)	12.8