

Specification Sheet

Part Number: 170-03055



Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver, 250 ft/bulk reel

Article Number 170-03055

Type BSHTTST34SRB

Color Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per reel

Product Description High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver, 250 ft/bulk reel
Global Part Name	BSHTTST34SRB-AL/GF-SR
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.687
Bundle Diameter Max (Metric)	17.4
Diameter D (imperial)	0.75
Diameter D (metric)	19.1
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	19.1
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64

Material	Aluminum (AL) Glass Fiber (GF)
Material Shortcut	GF AL
Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	7019905050
Weight (Metric)	3.91
Weight (Imperial)	8.625

