

## Specification Sheet

Part Number: 170-03055



Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver, 250 ft/bulk reel

**Article Number**

170-03055

**Type**

BSHTTST34SRB

**Color**

Silver (SR)

**Features & Benefits**

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

**Quantity Per**

reel

**Product Description**

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

**Short Description**

Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver, 250 ft/bulk reel

**Global Part Name**

BSHTTST34SRB-AL/GF-ML

**Length L (Imperial)**

250.0

**Length L (Metric)**

76.2

**Bundle Diameter Min (Imperial)**

0.1

**Bundle Diameter Min (Metric)**

2.54

**Bundle Diameter Max (Imperial)**

0.687

**Bundle Diameter Max (Metric)**

17.4

**Diameter D (imperial)**

0.75

**Diameter D (metric)**

19.1

**Nominal Diameter (Imperial)**

3/4

**Nominal Diameter (Metric)**

19.1

**Wall Thickness WT (Imperial)**

0.025

**Wall Thickness WT (Metric)**

0.64

**Material**

Glass Fiber (GF) Aluminum (AL)

**Material Shortcut**

AL GF

**Flammability**

Non-Flammable

**Halogen free**

Yes

**Operating Temperature (Metric)**

-76°F to +491°F (-60°C to +255°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

250

**Package Quantity (Metric)**

76.20

**Customs Number**

7019905050

**Weight (Metric)**

3.91

**Weight (Imperial)**

8.625