

Specification Sheet

Part Number: 170-03056



Braided Sleeving, Aluminum Laminated Fiberglass, 1" Dia, AL/GF, Silver, 250 ft/bulk reel

Article Number

170-03056

Type

BSHTTST10SRB

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per

reel

Product Description

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 1" Dia, AL/GF, Silver, 250 ft/bulk reel
Global Part Name	BSHTTST10SRB-AL/GF-ML
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.937
Bundle Diameter Max (Metric)	23.8
Diameter D (imperial)	1.0
Diameter D (metric)	25.4
Nominal Diameter (Imperial)	1
Nominal Diameter (Metric)	25.4
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64
Material	Glass Fiber (GF) Aluminum (AL)

Material Shortcut

GF AL

Flammability

Non-Flammable

Halogen free

Yes

Operating Temperature (Metric)

-76°F to +491°F (-60°C to +255°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

250

Package Quantity (Metric)

76.20

Customs Number

7019905050

Weight (Metric)

5.08

Weight (Imperial)

11.25