

Specification Sheet

Part Number: 170-03057



Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 100 ft/bulk reel

Article Number

170-03057

Type

BSHTTST134SRB

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per

reel

Product Description

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description

Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 100 ft/bulk reel

Global Part Name

BSHTTST134SRB-AL/GF-ML

Length L (Imperial)

100.0

Length L (Metric)

30.48

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

1.687

Bundle Diameter Max (Metric)

42.8

Diameter D (imperial)

1.75

Diameter D (metric)

44.4

Nominal Diameter (Imperial)

1-3/4

Nominal Diameter (Metric)

44.5

Wall Thickness WT (Imperial)

0.025

Wall Thickness WT (Metric)

0.64

Material

Aluminum (AL) Glass Fiber (GF)

Material Shortcut

AL GF

Flammability

Non-Flammable

Halogen free

Yes

Operating Temperature (Metric)

-76°F to +491°F (-60°C to +255°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

30.48

Customs Number

7019901000

Weight (Metric)

3.36

Weight (Imperial)

7.40