

Specification Sheet

Part Number: 170-03061



Braided Sleeving, Resin Coated Fiberglass, 1" Dia, GF, Black, 25 ft/reel

Article Number

170-03061

Type

BSHTFG100

Color

Black (BK)

Features & Benefits

- An exceptionally tough sleeving material which provides thermal protection up to 1,200°F.
- Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
- Cuts easily with ordinary scissors for easy application.
- UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.

Quantity Per

reel

Product Description

An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress. Perfect for engine manifolds and exhaust systems or any application where fire and exceeding temperatures create a hazard to workforce and equipment.

Short Description	Braided Sleeving, Resin Coated Fiberglass, 1" Dia, GF, Black, 25 ft/reel
Global Part Name	BSHTFG100-GF-BK
Length L (Imperial)	25.0
Length L (Metric)	7.62
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.625
Bundle Diameter Max (Metric)	41.3
Diameter D (imperial)	1.0
Diameter D (metric)	25.4
Nominal Diameter (Imperial)	1
Nominal Diameter (Metric)	25.4
Wall Thickness WT (Imperial)	0.057
Wall Thickness WT (Metric)	1.45
Material	Glass Fiber (GF)

Material Shortcut	GF
Flammability	UL VW-1
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +1202°F (-70°C to +650°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	25
Package Quantity (Metric)	7.62
Customs Number	7019901000
Weight (Metric)	1.2
Weight (Imperial)	2.61