

Specification Sheet

Part Number: 170-03063



Braided Sleeveing, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver 100 ft/reel

Article Number

170-03063

Type

BSHTTST34SR

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Product Description

High Temperature Aluminum Laminated Fiberglass Sleeveing is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description

Braided Sleeveing, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver 100 ft/reel

Global Part Name	BSHTTST34SR-AL/GF-ML
Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.687
Bundle Diameter Max (Metric)	17.5
Diameter D (imperial)	0.75
Diameter D (metric)	19.1
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	19.1
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64
Material	Aluminum (AL) Glass Fiber (GF)
Material Shortcut	AL GF

Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	7019901000
Weight (Metric)	1.57
Weight (Imperial)	3.45