

Specification Sheet

Part Number: 170-03063



Braided Sleeving, Aluminum Laminated Fiberglass, 0.75" Dia, AL/GF, Silver 100 ft/reel

Article Number 170-03063

Type BSHTTST34SR

Color Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Product Description

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description Braided Sleeving, Aluminum Laminated Fiberglass, 0.75" Dia, AL/GF, Silver 100 ft/reel

Global Part Name BSHTTST34SR-AL/GF-SR

Length L (Imperial) 100.0

Length L (Metric) 30.48

Bundle Diameter Min (Imperial) 0.1

Bundle Diameter Min (Metric) 2.54

Bundle Diameter Max (Imperial) 0.687

Bundle Diameter Max (Metric) 17.5

Diameter D (imperial) 0.75

Diameter D (metric) 19.1

Nominal Diameter (Imperial) 0.75

Nominal Diameter (Metric) 19.1

Wall Thickness WT (Imperial) 0.025

Wall Thickness WT (Metric) 0.64

Material Glass Fiber (GF) Aluminum (AL)

Material Shortcut	AL GF
Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	7019905050
Weight (Metric)	1.57
Weight (Imperial)	3.45