

Specification Sheet

Part Number: 170-03065



Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 50 ft/reel

Article Number

170-03065

Type

BSHTTST134SR

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per

reel

Product Description

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 50 ft/reel
Global Part Name	BSHTTST134SR-AL/GF-ML
Length L (Imperial)	50.0
Length L (Metric)	15.2
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.687
Bundle Diameter Max (Metric)	42.8
Diameter D (imperial)	1.25
Diameter D (metric)	31.8
Nominal Diameter (Imperial)	1-3/4
Nominal Diameter (Metric)	44.5
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64
Material	Glass Fiber (GF) Aluminum (AL)

Material Shortcut

GF AL

Flammability

Non-Flammable

Halogen free

Yes

Operating Temperature (Metric)

-76°F to +491°F (-60°C to +255°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

50

Package Quantity (Metric)

15.24

Customs Number

7019901000

Weight (Metric)

1.68

Weight (Imperial)

3.70