

Specification Sheet

Part Number: 170-03071



Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel

Article Number 170-03071

Type BSPFR188

Color Gray (GY)

Features & Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Quantity Per reel

Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description	Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel
Global Part Name	BSPFR188-PET-GY
Length L (Imperial)	225.0
Length L (Metric)	68.6
Bundle Diameter Min (Imperial)	0.094
Bundle Diameter Min (Metric)	2.4
Bundle Diameter Max (Imperial)	0.25
Bundle Diameter Max (Metric)	6.4
Diameter D (imperial)	0.13
Diameter D (metric)	3.2
Nominal Diameter (Imperial)	1/8
Nominal Diameter (Metric)	3.2
Material	Polyester (PET)
Material Shortcut	PET

Flammability	Mil-202 FAR 25 FMVSS 302 UL VW-1
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +257°F (-70°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 94 VW-1
UL Recognized (US)	Yes
Package Quantity(Imperial)	225
Package Quantity (Metric)	68.58
Customs Number	5808100000
Weight (Metric)	0.18
Weight (Imperial)	0.4