

## Specification Sheet

Part Number: 170-03072



Braided Sleeving, Expandable, Flame Retardant, .25" Dia, PET, Gray, 200 ft/reel

<b>Article Number</b>	170-03072
<b>Type</b>	BSPFR148
<b>Color</b>	Gray (GY)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.</li><li>• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

<b>Short Description</b>	Braided Sleeving, Expandable, Flame Retardant, .25" Dia, PET, Gray, 200 ft/reel
<b>Global Part Name</b>	BSPFR148-PET-GY
<b>Length L (Imperial)</b>	200.0
<b>Length L (Metric)</b>	61.0
<b>Bundle Diameter Min (Imperial)</b>	0.125
<b>Bundle Diameter Min (Metric)</b>	3.2
<b>Bundle Diameter Max (Imperial)</b>	0.437
<b>Bundle Diameter Max (Metric)</b>	11.1
<b>Diameter D (imperial)</b>	0.25
<b>Diameter D (metric)</b>	6.4
<b>Nominal Diameter (Imperial)</b>	1/4
<b>Nominal Diameter (Metric)</b>	6.4
<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Flammability</b>	Mil-202 FMVSS 302 FAR 25 UL VW-1

**Halogen free** Yes

**Operating Temperature (Metric)** -94°F to +257°F (-70°C to +125°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL 94 VW-1

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 200

**Package Quantity (Metric)** 60.96

**Customs Number** 5808100000

**Weight (Metric)** 0.22

**Weight (Imperial)** 0.48