

Specification Sheet

Part Number: 170-03072



Braided Sleeving, Expandable, Flame Retardant, .25" Dia, PET, Gray, 200 ft/reel

Article Number	170-03072
Type	BSPFR148
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
Quantity Per	reel
Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description

Braided Sleeving, Expandable, Flame Retardant, .25" Dia, PET, Gray, 200 ft/reel

Global Part Name

BSPFR148-PET-GY

Length L (Imperial)

200.0

Length L (Metric)

61.0

Bundle Diameter Min (Imperial)

0.125

Bundle Diameter Min (Metric)

3.2

Bundle Diameter Max (Imperial)

0.437

Bundle Diameter Max (Metric)

11.1

Diameter D (imperial)

0.25

Diameter D (metric)

6.4

Nominal Diameter (Imperial)

1/4

Nominal Diameter (Metric)

6.4

Material

Polyester (PET)

Material Shortcut

PET

Flammability

Mil-202 UL VW-1 FMVSS 302 FAR 25

Halogen free Yes

Operating Temperature (Metric) -94°F to +257°F (-70°C to +125°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL 94 VW-1

UL Recognized (US) Yes

Package Quantity(Imperial) 200

Package Quantity (Metric) 60.96

Customs Number 3926909987

Weight (Metric) 0.22

Weight (Imperial) 0.48