

## Specification Sheet

Part Number: 170-03092



Braided Sleeving, Expandable, Flame Retardant, 0.75" Dia, PET, Black, 250 ft/bulk reel

**Article Number** 170-03092

**Type** BSPFR340B

**Color** Black (BK)

**Features & Benefits**

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

**Quantity Per** reel

**Product Description**

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

<b>Short Description</b>	Braided Sleeving, Expandable, Flame Retardant, 0.75" Dia, PET, Black, 250 ft/bulk reel
<b>Global Part Name</b>	BSPFR340B-PET-BK
<b>Length L (Imperial)</b>	250.0
<b>Length L (Metric)</b>	76.2
<b>Bundle Diameter Min (Imperial)</b>	0.5
<b>Bundle Diameter Min (Metric)</b>	12.7
<b>Bundle Diameter Max (Imperial)</b>	1.25
<b>Bundle Diameter Max (Metric)</b>	31.8
<b>Diameter D (Imperial)</b>	0.75
<b>Diameter D (Metric)</b>	19.1
<b>Nominal Diameter (Imperial)</b>	0.75
<b>Nominal Diameter (Metric)</b>	19.1
<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET

<b>Flammability</b>	UL VW-1 Mil-202 FMVSS 302 FAR 25
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-94°F to +257°F (-70°C to +125°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL 94 VW-1
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	250
<b>Package Quantity (Metric)</b>	76.20
<b>Customs Number</b>	5808100000
<b>Weight (Metric)</b>	1.0
<b>Weight (Imperial)</b>	2.2