


Specification Sheet

Part Number: 170-03095



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.

Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Black, 200 ft/bulk reel

Article Number 170-03095

Type BSPFR1120B

Color Black (BK)

Quantity Per reel

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Black, 200 ft/bulk reel

Global Part Name BSPFR1120B-PET-BK

Length L (Imperial) 200.0

Length L (Metric) 61.0

Bundle Diameter Min (Imperial) 1.0

Bundle Diameter Min (Metric) 25.4

Bundle Diameter Max (Imperial) 2.125

Bundle Diameter Max (Metric) 54.0

Diameter D (Imperial) 1.5

Diameter D (Metric) 38.1

Nominal Diameter (Imperial) 1.5

Nominal Diameter (Metric) 38.1

Material Polyester (PET)

Material Shortcut PET

Flammability UL VW-1 FMVSS 302 FAR 25 Mil-202

Halogen Free Yes

Operating Temperature -94°F to +257°F (-70°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL 94 VW-1

UL Recognized (US) Yes

Package Quantity (Imperial) 200

Package Quantity (Metric) 60.96

Customs Number 5808100000