

Specification Sheet

Part Number: 170-03095



Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Black, 200 ft/bulk reel

Article Number

170-03095

Type

BSPFR1120B

Color

Black (BK)

Features & Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Quantity Per

reel

Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description

Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Black, 200 ft/bulk reel

Global Part Name

BSPFR1120B-PET-BK

Length L (Imperial)

200.0

Length L (Metric)

61.0

Bundle Diameter Min (Imperial)

1.0

Bundle Diameter Min (Metric)

25.4

Bundle Diameter Max (Imperial)

2.125

Bundle Diameter Max (Metric)

54.0

Diameter D (imperial)

1.5

Diameter D (metric)

38.1

Nominal Diameter (Imperial)

1-1/2

Nominal Diameter (Metric)

38.1

Material

Polyester (PET)

Material Shortcut

PET

Flammability

FAR 25 Mil-202 UL VW-1 FMVSS 302

Halogen free Yes

Operating Temperature (Metric) -94°F to +257°F (-70°C to +125°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL 94 VW-1

UL Recognized (US) Yes

Package Quantity(Imperial) 200

Package Quantity (Metric) 60.96

Customs Number 3926909987

Weight (Metric) 1.77

Weight (Imperial) 3.9