

Specification Sheet

Part Number: 170-03097



Braided Sleeving, Aluminum Laminated Fiberglass, 2.5" Dia, AL/GF, Silver, 50 ft/reel

Article Number 170-03097

Type BSHTTST212SR

Color Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per reel

Product Description High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 2.5" Dia, AL/GF, Silver, 50 ft/reel
Global Part Name	BSHTTST212SR-AL/GF-SR
Length L (Imperial)	50.0
Length L (Metric)	15.2
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	2.375
Bundle Diameter Max (Metric)	60.3
Diameter D (Imperial)	2.5
Diameter D (Metric)	63.5
Nominal Diameter (Imperial)	2.5
Nominal Diameter (Metric)	63.5
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64

Material	Aluminum (AL) Glass Fiber (GF)
Material Shortcut	GF AL
Flammability	Non-Flammable
Halogen Free	Yes
Operating Temperature	-76°F to +491°F (-60°C to +255°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	15.24
Customs Number	7019905050
Weight (Metric)	2.3
Weight (Imperial)	5.05