

Specification Sheet

Part Number: 170-03099



Plenum Rated Expandable Braided Sleeving (Halar), 0.12" Dia, White, 225 ft/reel

Article Number	170-03099
Type	BSHLR1810
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Resists gasoline and engine chemicals.•Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.•Expands up to 150% for economical and expeditious installation.•Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.•Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
Quantity Per	reel

Product Description

Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern. This sleeving is made from strands of high temperature, flame resistant Halar monofilaments that are able to resist a wide range of corrosive chemicals and organic solvents. Its low flame spread and smoke generation properties make it the perfect option for use in technologically advanced applications, such as those in the automotive, aerospace and vital military markets.

Short Description

Plenum Rated Expandable Braided Sleeving (Halar), 0.12" Dia, White, 225 ft/reel

Global Part Name

BSHLR1810-PA66E/CTFE-WH

Length L (Imperial)

225.0

Length L (Metric)

68.6

Width W (Imperial)

0.01

Width W (Metric)

.25

Bundle Diameter Min (Imperial)

0.094

Bundle Diameter Min (Metric)

2.4

Bundle Diameter Max (Imperial)

0.25

Bundle Diameter Max (Metric)

6.4

Diameter D (imperial)

0.13

Diameter D (metric)

3.1

Nominal Diameter (Imperial)

1/8

Nominal Diameter (Metric) 3.1

Material Ethylene Chlorotrifluoroethylene (E/CTFE)

Material Shortcut PA66E/CTFE

Flammability FAR 25 UL VW-1

Halogen free No

Operating Temperature (Metric) -103°F to +302°F (-75°C to +150°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL | UL 1441 UL | UL 746A UL 2024 UL | ANSI/UL 746B

UL Recognized (US) Yes

Package Quantity(Imperial) 225

Package Quantity (Metric) 68.58

Customs Number 3926909987

Weight (Metric) 0.27

Weight (Imperial) 0.56

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)