

## Specification Sheet

Part Number: 170-03123

Cuts with scissors without fraying ends enables field installations without need for hot knife.

Expands to 150% of easy installation and reduced assembly time requirements.

Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.



Braided Sleeving, Expandable, Fray Resistant, 0.125" Dia, PET, Black, 100 ft/reel

**Article Number** 170-03123

**Type** BSPSC180

**Color** Black (BK)

**Quantity Per** reel

**Product Description** A versatile and economical general purpose sleeving that resists fraying when cut with ordinary scissors. For use in automotive, industrial and computer applications where the wires, cables and hoses being covered endure frequent handling. It is suited for situations where access to a hot knife is either impractical or impossible.

**Short Description** Braided Sleeving, Expandable, Fray Resistant, 0.125" Dia, PET, Black, 100 ft/reel

**Global Part Name** BSPSC180-PET-BK

**Length L (Imperial)** 100.0

**Length L (Metric)** 30.48

**Bundle Diameter Min (Imperial)** 0.125

**Bundle Diameter Min (Metric)** 3.2

**Bundle Diameter Max (Imperial)** 0.25

**Bundle Diameter Max (Metric)** 6.4

**Diameter D (Imperial)** 0.25

**Diameter D (Metric)** 6.4

**Nominal Diameter (Imperial)** 0.125

**Nominal Diameter (Metric)** 3.18

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL 94 V-0

<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-94°F to +257°F (-70°C to +125°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	5808100000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)