

## Specification Sheet

Part Number: 170-03128



Braided Sleeving, Split Wrap, 1" Dia, PET, Black, 100 ft/bulk reel

**Article Number**

170-03128

**Type**

BSPSW100B

**Color**

Black (BK)

**Features & Benefits**

- Center-slit overlapping design allows quick and easy access to the wires and cables for future maintenance or inspection without disassembly.
- Flexible material allows it to easily wrap around a variety of component shapes and sizes, making it easier to use than slit-loom tubing or spiral-wrap materials.
- A unique weave pattern provides increased coverage and greater resistance to abrasion, dust and debris.
- Overlapping design enhances flexibility, allowing it to shift and bend without exposing wire and cables.

**Quantity Per**

box

**Product Description**

Split Wrap Woven Sleeving is a self-closing sleeving manufactured from a unique blend of monofilament and multifilament polyester fibers that resemble a tightly woven material. The wrap around design provides increased flexibility, better coverage and greater resistance from abrasion for wires, cables and assemblies. Can also be used to reduce noise in applications that involve movement, while protecting sensitive electronics and communication systems from dust and debris.

**Short Description**

Braided Sleeving, Split Wrap, 1" Dia, PET, Black, 100 ft/bulk reel

**Global Part Name**

BSPSW100B-PET-BK

**Length L (Imperial)**

100.0

**Length L (Metric)**

30.48

**Bundle Diameter Min (Imperial)**

0.1

**Bundle Diameter Min (Metric)**

2.54

**Bundle Diameter Max (Imperial)**

1.0

**Bundle Diameter Max (Metric)**

25.4

**Diameter D (imperial)**

1.0

**Diameter D (metric)**

25.4

**Nominal Diameter (Imperial)**

1

**Nominal Diameter (Metric)**

25.4

**Wall Thickness WT (Imperial)**

0.038

**Wall Thickness WT (Metric)**

0.97

<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Flammability</b>	UL 94 V0
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-94°F to +257°F (-70°C to +125°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	30.48
<b>Customs Number</b>	3926909987
<b>Weight (Metric)</b>	0.91
<b>Weight (Imperial)</b>	2.0

