

## Specification Sheet

Part Number: 170-03135



Braided Sleeving, Split Wrap, .75" Dia, PET, Black, 500 ft/bulk reel

**Article Number**

170-03135

**Type**

BSPSW340LB

**Color**

Black (BK)

### Features & Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

**Quantity Per**

reel

### Product Description

A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

**Short Description**

Braided Sleeving, Split Wrap, .75" Dia, PET, Black, 500 ft/bulk reel

**Global Part Name**

BSPSW340LB-PET-BK

**Length L (Imperial)**

500.0

**Length L (Metric)**

152.4

**Bundle Diameter Min (Imperial)**

0.1

**Bundle Diameter Min (Metric)**

2.54

**Bundle Diameter Max (Imperial)**

0.75

**Bundle Diameter Max (Metric)**

19.1

**Diameter D (imperial)**

0.75

**Diameter D (metric)**

19.1

**Nominal Diameter (Imperial)**

3/4

**Nominal Diameter (Metric)**

19.1

**Wall Thickness WT (Imperial)**

0.025

**Wall Thickness WT (Metric)**

0.64

**Material**

Polyester (PET)

**Material Shortcut**

PET

**Flammability**

UL 94 V0

**Halogen free**

Yes

**Operating Temperature (Metric)**

-94°F to +257°F (-70°C to +120°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

152.40

**Customs Number**

3926909987

**Weight (Metric)**

7.6

**Weight (Imperial)**

16.8