

Specification Sheet

Part Number: 170-03145



Braided Sleeving, Split Wrap, Flame Retardant, 1.25" Dia, PET, Black, 75 ft/bulk reel

Article Number 170-03145

Type BSSWFR1140B

Color Black (BK)

Features & Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout operating temperature range.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
- Self wrapping design eliminates the need for fasteners.
- Provides a greater flexibility than spiralwrap or convoluted tubing.

Quantity Per reel

Product Description	Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.
Short Description	Braided Sleeving, Split Wrap, Flame Retardant, 1.25" Dia, PET, Black, 75 ft/bulk reel
Global Part Name	BSSWFR1140B-PET-BK
Length L (Imperial)	75.0
Length L (Metric)	22.9
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.8
Diameter D (imperial)	1.25
Diameter D (metric)	31.8
Nominal Diameter (Imperial)	1-1/4
Nominal Diameter (Metric)	31.8

Wall Thickness WT (Imperial)	0.038
Wall Thickness WT (Metric)	0.97
Material	Polyester (PET)
Material Shortcut	PET
Flammability	Low Smoke Generation Halogen-Free Limited Fire Hazard UL VW-1 Low generation of toxic gases and corrosive acid FAR 25
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +257°F (-70°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	75
Package Quantity (Metric)	22.86
Customs Number	5808100000

Weight (Metric) 0.82

Weight (Imperial) 1.8