

## Specification Sheet

Part Number: 170-03146



Split wrap design installs quickly, saving assembly time and future accessibility without disassembly. Unique construction retains shape and rigidity throughout operating temperature range. Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations. Self wrapping design eliminates the need for fasteners. Provides a greater flexibility than spiralwrap or convoluted tubing.

Braided Sleeving, Split Wrap, Flame Retardant, 1.5" Dia, PET, Black, 75 ft/bulk reel

<b>Article Number</b>	170-03146
<b>Type</b>	BSSWFR1120B
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	box

### Product Description

Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

<b>Short Description</b>	Braided Sleeving, Split Wrap, Flame Retardant, 1.5" Dia, PET, Black, 75 ft/bulk reel
<b>Global Part Name</b>	BSSWFR1120B-PET-BK
<b>Length L (Imperial)</b>	75.0
<b>Length L (Metric)</b>	22.9
<b>Bundle Diameter Min (Imperial)</b>	0.1
<b>Bundle Diameter Min (Metric)</b>	2.54
<b>Bundle Diameter Max (Imperial)</b>	1.5
<b>Bundle Diameter Max (Metric)</b>	38.1
<b>Diameter D (Imperial)</b>	1.50
<b>Diameter D (Metric)</b>	38.1
<b>Nominal Diameter (Imperial)</b>	1.5
<b>Nominal Diameter (Metric)</b>	38.1
<b>Wall Thickness WT (Imperial)</b>	0.038
<b>Wall Thickness WT (Metric)</b>	0.97

<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Flammability</b>	FAR 25 Limited Fire Hazard Low Smoke Generation Low generation of toxic gases and corrosive acid UL VW-1 Halogen-Free
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-94°F to +257°F (-70°C to +125°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	ASTM E 162 Exova   NFPA130: 2017 ASTM 1354 ASTM E 662
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	75
<b>Package Quantity (Metric)</b>	22.86
<b>Customs Number</b>	5808100000