

## Specification Sheet

Part Number: 170-03146


Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.

Unique construction retains shape and rigidity throughout operating temperature range.

Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Self wrapping design eliminates the need for fasteners.

Provides a greater flexibility than spiralwrap or convoluted tubing.



Braided Sleeving, Split Wrap, Flame Retardant, 1.5" Dia, PET, Black, 75 ft/bulk reel

Article Number 170-03146

Type BSSWFR1120B

Color Black (BK)

Quantity Per box

**Product Description**

Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

|                                |  |
|--------------------------------|--|
| Short Description              | Braided Sleeving, Split Wrap, Flame Retardant, 1.5" Dia, PET, Black, 75 ft/bulk reel |
| Global Part Name               | BSSWFR1120B-PET-BK   |
| Length L (Imperial)            | 75.0   |
| Length L (Metric)              | 22.9   |
| Bundle Diameter Min (Imperial) | 0.1  |
| Bundle Diameter Min (Metric)   | 2.54   |
| Bundle Diameter Max (Imperial) | 1.5  |
| Bundle Diameter Max (Metric)   | 38.1   |
| Diameter D (Imperial)          | 1.50   |
| Diameter D (Metric)            | 38.1   |
| Nominal Diameter (Imperial)    | 1.5  |
| Nominal Diameter (Metric)      | 38.1   |
| Wall Thickness WT (Imperial)   | 0.038  |
| Wall Thickness WT (Metric)     | 0.97   |

|                              |                                   |
|------------------------------|-----------------------------------|
| Material                     | Polyester (PET)                   |
| Material Shortcut            | PET                               |
| Flammability                 | UL 224 VW-1 FAR 25                |
| Halogen Free                 | Yes                               |
| UV Resistant (Yes/No)        | No                                |
| Operating Temperature        | -94°F to +257°F (-70°C to +125°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Certification/Specification  | ASTM E 662 ASTM E 162 ASTM 1354   |
| UL Recognized (US)           | Yes                               |
| Package Quantity (Imperial)  | 75                                |
| Package Quantity (Metric)    | 22.86                             |
| Customs Number               | 5808100000                        |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin.  
([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)