

Specification Sheet

Part Number: 170-03183



Braided Sleeving, Split Wrap, 5/8" Dia, PET, Black, 250 ft/bulk reel

Article Number

170-03183

Type

BSSWV580B

Color

Black (BK)

Features & Benefits

- Split wrap design needs no fasteners and installs quickly, saving assembly time and future accessibility without disassembly.
- Bends to a tight radius without distortion or splitting open.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick access and ability to apply protective sleeving post assembly or post installation situations.

Quantity Per

reel

Product Description

A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires. More flexible than spiral wraps or convoluted tubing, this product is a fast and easy option for adding protection in post-assembly or post-installation applications.

Short Description	Braided Sleeving, Split Wrap, 5/8" Dia, PET, Black, 250 ft/bulk reel
Global Part Name	BSSWV580B-PET-BK
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.63
Bundle Diameter Max (Metric)	15.8
Diameter D (imperial)	0.63
Diameter D (metric)	16.0
Nominal Diameter (Imperial)	5/8
Nominal Diameter (Metric)	15.8
Wall Thickness WT (Imperial)	0.027
Wall Thickness WT (Metric)	0.68
Material	Polyester (PET)

Material Shortcut

PET

Flammability

UL 94 V0

Halogen free

Yes

Operating Temperature (Metric)

-94°F to +257°F (-70°C to +125°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

UL Recognized (US)

Yes

Package Quantity(Imperial)

250

Package Quantity (Metric)

76.20

Customs Number

5806322000

Weight (Metric)

2.38

Weight (Imperial)

5.25