

## Specification Sheet

Part Number: 170-03192



Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 0.5" Dia, AL/GF, Silver, 25/box

**Article Number** 170-03192

**Type** BSHTTSW12SB

**Color** Silver (SR)

**Features & Benefits**

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

**Quantity Per** box

**Product Description**

Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. Sold in 4-foot sticks.

<b>Short Description</b>	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 0.5" Dia, AL/GF, Silver, 25/box
<b>Global Part Name</b>	BSHTTSW12SB-GF-AL-SR
<b>Length L (Imperial)</b>	4.0
<b>Length L (Metric)</b>	1.22
<b>Bundle Diameter Min (Imperial)</b>	0.1
<b>Bundle Diameter Min (Metric)</b>	2.54
<b>Bundle Diameter Max (Imperial)</b>	0.45
<b>Bundle Diameter Max (Metric)</b>	11.4
<b>Diameter D (Imperial)</b>	0.5
<b>Diameter D (Metric)</b>	12.7
<b>Nominal Diameter (Imperial)</b>	0.5
<b>Nominal Diameter (Metric)</b>	12.70
<b>Wall Thickness WT (Imperial)</b>	0.042
<b>Wall Thickness WT (Metric)</b>	1.06

<b>Material</b>	Glass fiber with aluminium foil (GF-AL)
<b>Material Shortcut</b>	GF-AL
<b>Flammability</b>	Non-Flammable
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-76°F to +491°F (-60°C to +255°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	7019905050