

Specification Sheet

Part Number: 170-03196



A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.

Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.

Cuts with ordinary scissors for fast, easy application.

Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 1.25" Dia, AL/GF, Silver, 6/box

Article Number	170-03196
Type	BSHTTSW114SB
Color	Silver (SR)
Quantity Per	box
Product Description	Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. Sold in 4-foot sticks.
Short Description	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 1.25" Dia, AL/GF, Silver, 6/box

Global Part Name BSHTTSW114SB-GF-AL-SR

Length L (Imperial) 4.0

Length L (Metric) 1.22

Bundle Diameter Min (Imperial) 0.1

Bundle Diameter Min (Metric) 2.54

Bundle Diameter Max (Imperial) 1.20

Bundle Diameter Max (Metric) 30.5

Diameter D (Imperial) 1.25

Diameter D (Metric) 31.75

Nominal Diameter (Imperial) 1.25

Nominal Diameter (Metric) 31.75

Wall Thickness WT (Imperial) 0.042

Wall Thickness WT (Metric) 1.06

Material Glass fiber with aluminium foil (GF-AL)

Material Shortcut	GF-AL
Flammability	Non-Flammable
Halogen Free	Yes
Operating Temperature	-76°F to +491°F (-60°C to +255°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	6
Package Quantity (Metric)	6
Customs Number	7019905050