

Specification Sheet

Part Number: 170-03202



Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 1.5" Dia, AL/GF, Silver, 15/box

Article Number 170-03202

Type BSHTTSW112LB

Color Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Quantity Per box

Product Description

Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. Sold in 4-foot sticks.

Short Description	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 1.5" Dia, AL/GF, Silver, 15/box
Global Part Name	BSHTTSW112LB-GF-AL-SR
Length L (Imperial)	4.0
Length L (Metric)	1.22
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.8
Diameter D (Imperial)	1.5
Diameter D (Metric)	38.1
Nominal Diameter (Imperial)	1.5
Nominal Diameter (Metric)	38.1
Wall Thickness WT (Imperial)	0.042
Wall Thickness WT (Metric)	1.06

Material	Glass fiber with aluminium foil (GF-AL)
Material Shortcut	GF-AL
Flammability	Non-Flammable
Halogen Free	Yes
Operating Temperature	-76°F to +491°F (-60°C to +255°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	15
Package Quantity (Metric)	15
Customs Number	7019905050